

TECHNICAL DATA SHEET

Revision date: 27.02.2019

HOLLOW SECTION WAX

Article number: 37815

Intended use: Car refinishing product/ Protective coating

General characteristics: CHAM'ALEON HOLLOW SECTION WAX is a protective coating which protects against corrosion. It is based on special waxes which conserve and seal car body cavities. Thanks to its excellent penetrating properties, moisture is displaced even from small corners and seams. Due to its consistency the wax doesn't drip or run.

Color: Transparent brown

Hardener: --

Mixing ratio: --

Dilution: Ready to spray

Spraying viscosity 4 mm DIN: --

Application method

Application method	Pressure	Nozzle
UBS spray gun	4 - 6 bar	5 - 10 mm

Processing conditions:

only use in a well ventilated workspace. Working temperature must be at least +10 °C. Max. air humidity 80 %.

Spraying operations	DFT	Consumption
1 - 2	--	--

Drying

Object temperature 20 °C: --

Pot life at 20 °C: --



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 448 g/l.

Processing tips:

Shake well before use.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.