



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

#### TECHNICAL DATA SHEET

### CHAMÄLEON PRE-FILL

**Article number:** 25001

**Intended use:** Car refinishing Product/ Preparation

General characteristics:

Chamäleon pre-fill standard is a pre-filled can with propellant gases and solvent that can be filled with solvent-based basecoats. Ideal for spot

repairs or refinishing parts.

### **Product characteristics:**

- A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)
- Simple, time-saving application
- Excellent atomisation
- Light blending

# Physical and Chemical Characteristics:

**Colour**: depending on filling

Smell: solvent

Efficiency: Depending on consistence and colour of the ground

Substrate: Depending on the colour of the substrate apply Primer Filler, 2K Primer Filler,

1K Epoxy Primer, cured paint sanded

**Drying time** (at 20°C, 50% relative air humidity): The drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)

**Storage stability:** empty cans: 5 years. Filled cans: depending on type of paint from several hours up to 6 month (information from your specialist dealer). If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)

Size: Aerosol cans, maximum nominal volume 400 ml.

VOC-value: 218g





CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

### **Usage:**

Before use, carefully read the directions on the packaging and act accordingly.

- Clean the surface to be painted thoroughly with Chamaeleon silicone remover, then sand
- Larger bare surfaces must be pre-primed with the appropriate Chamaeleon primer
- The area must be dry and free of dust and grease
- Shake the can vigorously for 2 minutes
- Carry our spray test
- Compatibility testing is necessary
- For professional use only
- Wear an appropriate respirator (recommended type A2/P3)

## **Environment and labelling**

**Environmentally sound:** The products are 100% free of heavy metals.

The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.