



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL INFO@CHAMAELEON-PRODUKTION.DE  
WEB WWW.CHAMAELEON-PRODUKTION.DE

## TECHNICAL DATA SHEET (Provisional)

# LASER Perfect Shine Liquid Glaze

### Product Description

LASER Perfect Shine has been developed as a high gloss finishing glaze applied by either hand or machine for use on all paint systems (fresh – well cured). Perfect Shine has a very light cutting effect.

### Product Information

Size	Product Code	Carton Quantity
500 ml	49903	12 pcs

### Applications

Use with foam or by hand application

### Characteristics

- Water based
- High gloss
- Silicone free
- Recommended with foam or hand application.
- Ready to use.
- Dry use

### Physical Properties

State	Liquid
Colour	Blue
Relative Density	1.05
Viscosity	23,000cps
Flash Point	>93°C
pH	7-8
VOC Content g/l	Refer to SDS



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL INFO@CHAMAELEON-PRODUKTION.DE  
WEB WWW.CHAMAELEON-PRODUKTION.DE

## Storage & Handling

Store at room temperature  
Protect from frost  
Shake container prior to use

## Directions For Use

*For use by hand application only:*

1. Shake the bottle and apply a small amount to a clean Finishing Cloth.
2. Using light pressure apply the glaze to the panel using a circular overlapping action to ensure even coverage.
3. Buff the surface to a durable high gloss finish using a Finishing Cloth.

*For use by machine application only:*

1. Attach the Polishing Foam to a polishing machine and set to a free running speed of 1000-1500 rpm.
2. Apply a small amount of Perfect Shine to the paint surface and spread uniformly over the surface using the Polishing Foam before starting the machine to reduce splatter
3. Run lightly over the polishing area with the Polishing Foam kept flat until the desired gloss level has been achieved.
4. Remove any residue with a Finishing Cloth.

## Additional Information

Professional users may refer to the Safety Data Sheet for this product

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:  
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.