

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

Revision date: 30.01.2022

1

TECHNICAL DATA SHEET

LASER ULTIMATE FINISH

Article number: 49933

Colour: Grey

Intended use: Car refinishing product/ Automotive care products

General characteristics: Anti Haze Compound for the long-lasting removal of

haze and holograms on dark paint work.

Properties: The extreme fine grains guarantee reliable removal of the smallest paint imperfections and micro

scratches.

Physical properties and analytic data:

Physical state: Liquid

Odour: fruity

Initial boiling point and boiling range: 100

Flash point: >90

Ignition temperature in °C: >200 **VOC-value:** 13,507 % (133,721 g/l)

bH: 8

Viscosity: 8000-13000 Relative density: 0,99

Technical data:

Cutting power	2 - Fine
Gloss level	5 - Brilliant
Sand paper	P3000

Application:

Shake well before use. Apply a few drops on a not too soft polishing pad and a small amount on the to be treated surface. Use more polish if the polishing pad is dry. Position the polishing pad and start the machine (rotating or orbital) (1500-2000 1/min). Sporadic holograms can be processed manually by



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

using a polishing cloth. Remove any polish residue with a micro fibre cloth.

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Shelf-life and storage conditions:

Shelf-life: 2 years

Storage temperature: 15°C - 25°C.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under: e-mail: info@chamaeleon-produktion.de
For safety information, please refer to the corresponding safety data sheet.