



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL INFO@CHAMAELEON-PRODUKTION.DE  
WEB WWW.CHAMAELEON-PRODUKTION.DE

## TECHNICAL DATA SHEET

### ACRYLIC FILLING PRIMER HS 5+1

**Article number:** 14881, 14882, 14883, 14884, 14885, 14886, 14887,  
14888, 14889, 148880, 148890

**Intended use:** Car refinishing Product/ Filler

**General characteristics:** Chamäleon 5+1 HS Optimal is a fast-sand able 2K Compact filler with high corrosion resistance, high filling capacity and good adhesion for automotive refinishing. Also, the filling of patches (spot repair) is possible without sagging and edges margins.  
Coverage: 5-6 m<sup>2</sup> / l

**Substrate pre-treatment:**



sand

**Application:**

**Mixing ratio:** 5:1 by volume with Chamaeleon Acrylic Hardener  
**Pot life:** 1-5 hours

**Application:** conventional



gravity-feed

**Thinners:** 15 - 20 % , **wet on wet method 30 - 40 %**

**Application viscosity:** 30 - 55 seconds DIN 4/20°C



**Spray nozzle:** 1,4 - 1,9 mm

**Spraying pressure:** 2,5 - 4,5 bar



**Number of coats:** 1 - 3



**Flash off between the coats:** 15 min



**Drying:**

<b>Air drying at 20°C:</b>			
		120 – 180 micron	6 – 8 hours at 20°C
<b>Baking:</b>			
	flash off time		10 – 15 minutes
	drying	120 – 180 micron	30-40 minutes at 60°C

**Sanding:**

grind (with sandpaper P 400 for dry or P 600 for wet sanding for one-coat finishes, for two-coat finishes use P 500 for dry and P 800 is recommended for wet sanding)

**Remarks:**

Process conditions: from + 10° C and up to 75% air relative humidity.

Storage: at least 3 years if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:  
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.