

TECHNICAL DATA SHEET*Revision date: 30.03.2021***ISOLATOR PRIMER**

| | |
|---|--|
| Article number: | 26723 |
| Colour: | Beige |
| Intended use: | Car refinishing product/ Lacquer |
| General characteristics: | <p>Nitro-acrylic filler to repair small scratches and imperfections on interior and exterior surfaces. It creates a smooth and even surface, ideal for subsequent painting applications. Available in matt version.</p> <p>Main surfaces: ferrous and non-ferrous surfaces, wood in general. Suitable for car, motorcycle, moped, bicycle bodywork.</p> <p>Quick drying primer ready for use, it prevents from lifting and bleeding of old paint which are sensitive to strong solvents</p> |
| Quality and properties: | <p>Quick drying, high coverage, good adherence, easy to apply, filling, sandable, it improves adhesion for the top-coat, free of pigments containing heavy metals and harmful gases for the environment.</p> |
| Properties: | |
| Aspect and finish: | matt |
| Theoretical output at the suggested thickness sq m/package (400 ml): | 4 crossed coats - 0.8-1.2 m ² |
| Outdoors / indoors (exposure of the painted object): | yes / yes |
| Application process: | |
| Surface preparation: | <p>The surface must be dry, dust and fat free. Remove last traces of oil/grease with silicone remover. Before use, carefully read and observe the warning texts on the label!</p> |

■ **Important notes:**

If the scratch or imperfections to repair are deep, apply more coats, waiting at least 15 minutes between applications.

Warning! DO NOT DEGREASE the surface after applying the Isolator primer, as this is a one-component, reversible product, - the material can be removed with a degreaser.

| Drying | | Dry to touch | Full dry time |
|--------------------|-------------------------------------|--------------|---|
| Object temperature | 20 °C, 60% relative air humidity | 10 - 15 min. | 24 h / 36 h according to the thickness |

Environment and labelling

Environmentally sound: Isolator primer is 100% free of heavy metals. The caps and packaging are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.