



## ***TECHNICAL DATA SHEET***

### **AEROSOL UNDERBODY PROTECTION PREMIUM**

**Article number:** 38015 (white), 38025 (grey), 38035 (black)

**Intended use:** Car refinishing product/ Anticorrosion additive

**General characteristics:** Highly quality sprayable preservative against chippings to treat the underside and visible parts of the motor vehicles. Can be applied to zinc coated surfaces.

**Product characteristics:**

- Re-sprayable with all lacquer systems
- Remains flexible
- Very good adhesion
- Resistant to weather influences
- Resistant to weak acids and bases
- Excellent corrosion prevention
- Sound-absorbing

**Physical and chemical characteristics:**

Contents: 500 ml  
VOC-content: Approximately 74% w/w  
Dust dry: After approx. 30 minutes  
Tack free: After approx. 60 minutes  
Re-sprayable: After 2 hours

**Usage:**

**Before use, carefully read the directions on the packaging and act accordingly.**

**Pre Treatment**

Remove loose old lacquer and rust and sand the surface.

**Treatment**

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL [INFO@CHAMAELEON-PRODUKTION.DE](mailto:INFO@CHAMAELEON-PRODUKTION.DE)  
WEB [WWW.CHAMAELEON-PRODUKTION.DE](http://WWW.CHAMAELEON-PRODUKTION.DE)

Apply the UB protection premium in several layers. After drying, **without sanding**, re-sparable with all lacquer systems.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:  
[info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.