



TECHNICAL DATA SHEET

CHAMÄLEON BITUM SPRAY

Article number:	37100
Intended use:	Car refinishing Product/ Preparation
General characteristics:	High quality preservative to treat the underside of vehicles
Product characteristics:	<ul style="list-style-type: none">• Remains flexible• Excellent adhesion• Resistant to weather influences• Resistant to weak acids and bases• Excellent corrosion prevention• Sound-absorbing

Physical and Chemical

Contents
Colour
VOC-content
Dust dry

Characteristics

500 ml
Black
Approximately 70% w/w
After approximately 60 minutes

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment:

Remove loose old lacquer and rust and sand the surface.

Treatment:

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the undercoating in several layers.



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

After use:

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.