



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

CHAMÄLEON SPOT BLENDER AEROSOL

Article number:	26504
Intended use:	Car refinishing Product/ Preparation
General characteristics:	High quality mixture of solvents to level the transition at spot repairs.
Product characteristics:	<ul style="list-style-type: none">• Directed jetspray• Fine spray• As a result of the blending of the overspray, a smooth transition is obtained between the old and the new• lacquer• Instant (in)visible result

Physical and Chemical

Characteristics

Contents	150 ml
VOC-content	Approximately 99,5 % w/w

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol.

The Spotblender can be applied when the lacquer is tack free.

Spray the surface with spotblender till the overspray blends like a film.

The drying time depends on the ambient temperature and the humidity of the air.

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.