



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

Date of issue 24.02.2017

HOLLOW SECTION WAX

Article number: 26740

Intended use: Car refinishing Product/ Anticorrosion additive

Product description: High quality preservative to treat the hollow spaces in vehicle bodywork.

Product characteristics:

- Excellent corrosion prevention
- Excellent adhesion
- Resistant to weather influences
- Resistant to weak acids and bases
- Good penetrating quality

Physical and Chemical Characteristics:

Contents : 500 ml
Colour : White transparent
VOC-content : Approximately 77% w/w

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes.

Apply the wax generously in the hollow areas by means of the adapter.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.