

TECHNICAL DATA SHEET

Revision date: 20.04.2018

LEATHER PAINT SPRAY

- Article number:** 26801
- Intended use:** Car refinishing product/ Colour spray for smooth leather
- Product description:** High quality leather spray to repair and embellish parts of leather, vinyl and artificial leather.
- Product characteristics:**
- Lasting colour and lasting gloss
 - Elastic
 - Excellent adhesion
 - Maintains the original structure

Physical and Chemical Characteristics:

Contents:	200 ml
Base:	Nitro-cellulose binder
VOC-content:	Approximately 84% w/w
Solid content:	Approximately 16% w/w
Gloss:	Satin matt Coverage : 0,50 to 1,00 m ²
Dust free:	After 5 to 10 minutes
Tack free:	After 10 to 20 minutes
Hardened/re-sprayable:	After 2 hours
Heat resistant:	To 50°C

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface should be clean, dry and free of grease.

Treatment:

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the vinyl spray in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.